# Technical Data Sheet

LAST UPDATE: (January 2016)

# **SUPERGRIP**

Non-slip Additive

#### **DESCRIPTION**

Supergrip is clear non-slip additive that will take on the color of the sealer and the color of the concrete underneath unlike other materials in the market that leave a white or brown color.

Supergrip is harder than sand and will not crush easily, therefore it doesn't compromise the coating.

The unique light reflecting qualities of Supergrip adds a bit of sparkle to your surface, without changing the color of the coating. Use as much or as little as desired to create the perfect non-slip surface and effect.

Simply broadcast Supergrip onto your wet coating to provide excellent traction to any surface. Supergrip is desirable for any location in which a non-slip surface is required, such as pools, steps, decks or ramps.

Supergrip is available in #15, #17, #20, and #25 sizes. Supergrip is economically priced and available in 3 lb bottles and 50 lb pails. Meets LEED Requirements.

#### **BENEFITS**

Superior traction
Adds sparkle (reflects light)
Clear (transparent)
Economical
Easy to apply
VOCs - 0
Does not discolor decorative concrete

### **USES**

Non-slip additive for any coating Using Supergrip with any clear coating will give the coating sparkle Can be used directly in concrete

#### **EPOXY INSTRUCTIONS**

Apply the 1st coat of Epoxy. While still wet, broadcast Supergrip evenly over the entire surface. Once dry, apply the 2<sup>nd</sup> coat of Epoxy.

**Or** add 1 litre of Supergrip to a 4 litre kit of Epoxy, and mix thoroughly before applying.

#### **ACRYLIC INSTRUCTIONS**

Apply first coat of Premium Acrylic.
Broadcast Supergrip evenly over entire surface while the acrylic is still wet. Apply a second coat of Premium Acrylic once the first coat is dry. This will lock in the Supergrip. Supergrip will take on the color of the concrete and is transparent.

## **MESH SIZES**

Supergrip #30 (20-30) Supergrip #20 (30-80) Supergrip #15 (40-50) Supergrip #17 (70-100)

# WARRANTY

We warrant our products to be of good quality and will replace any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. The user shall determine the suitability of the product for the intended use and assume all risks and liability in connection therewith. Therefore, except for such replacement of product, Cornerstone Coatings makes no warranty or guarantee express or implied including warranties of fitness for a particular purpose or merchantability, respecting its products, and Cornerstone Coatings shall have no other liability with respect thereto. This warranty supersedes all other warranties express or implied.