

Protec III: Acrylic Membrane

The Complete Strength Gain Material
for New Concrete Floors

DESCRIPTION

Protec III: Acrylic Membrane is a high- end densifier with Acrylic Membrane used on existing interior concrete to dustproof and to give the concrete an attractive semi-gloss finish.

Protec III: Acrylic membrane works on 3 levels, which give it the clear and distinct advantage for concrete floors. Protec III: Acrylic Membrane is easy to apply, because we use Liquid Silica Fume Technology and not silicates or siliconates, which are highly temperamental and difficult to work with. Protec III: Acrylic Membrane is easily incorporated into the surface to increase the strength, hardness and micro-density of the concrete.

Protec III: Acrylic Membrane incorporates a high-end acrylic component to give a proper cure, virtually eliminating warping and topical cracking. Other products do not have this full cure capability, and the slab will show the tell-tale damaging signs of topical shrinkage cracking and warping. Winter heating environments often produce dusting of the concrete, using Protec III: Acrylic Membrane will protect the surface from exposure to achieve a proper cure and eliminate dusting.

Protec III: Acrylic Membrane is less costly because the easy to use formulation eliminates the need for expensive and overpriced certified installers.

PACKAGING

18.9 Litre Pail
205 Litre Drum

BENEFITS

Cures concrete to help stop shrinkage cracking and curling.
Helps eliminate dusting and stops carbonation of concrete.
Increases the chemical resistance and hardness of concrete.
Environmentally Safe and Permanent
Meets **LEED** Requirements
Abrasion Resistant (ASTM C418 Increased resistance to abrasion by 67%)
ASTM C309 Curing Type I Class A
FOOD SAFE – APPROVED
Non-Toxic

USES

For Interior Use Only
Use on all new power trowel concrete floors.
Use on interior existing concrete as a hardener and sealer.
Not compatible with flooring adhesives.

PHYSICAL

CHARACTERISTICS Physical

State: Liquid
Color: White
Odor: Slight Odor
VOC's: 9.5 grams/litre

SAFETY

Protec III: Acrylic Membrane is not toxic or dangerous to the health of installers or surrounding workers unlike solvent based cures or the carcinogenic dust from dry shake hardeners.

CAUTION

Protect surrounding area from over-spray. In case of accidental contact, rinse thoroughly with water immediately.
Do not apply to frozen surfaces. For best results apply when the substrate and ambient air temperature is above 53°F (12°C). For surfaces not specified, we recommend testing a small area to observe for possible adverse reactions.
DO NOT FREEZE Product.

SHELF LIFE: 2 years in original unopened container.

CAUTION: FOR HEAVY ABRASION FLOORS
(ie. Tracked in gravel and dirt that is being ground into the floor by forklifts)

FOLLOW THESE INSTRUCTIONS: Using Protec III Chem RX apply one coat to the areas that will be affected, let product dry.

For 2nd coat apply Protec III: Acrylic Membrane using the normal application procedure. Normal wear and tear does not include heavy abrasion from gravel and dirt, therefore it is highly recommended to keep your floors clean to avoid unnecessary excessive wear.

STANDARDS

ASTM C418 Abrasion – 67% increase in hardness of the concrete wear surface. ASTM C309 Curing, Type I, Class A

FLOOR CLASSIFICATIONS ACI 302, Class Numbers (1,3,4,5,6,7,8,9) floors Exceptions: #3 second course only, #3,4, no if covered surface, #7 second course only, #8 second course only, #9 if topping please consult Technical Support. Works well for super flat floors.

ASTM C642 –72% decrease in absorption.

SURFACE PREPARATION

New or existing concrete should be clean.

APPLICATION

Apply product with a low pressure sprayer or roller within 4 - 8 hours once finishing operations are done.

Apply at recommended square foot coverage.

Saw cuts need to be coated thoroughly.

Apply 1 coat at the recommended rate.

Roll out any puddles that form.

Drytime: 4 hours at 68°F (20°C)

Either roll or spray.

Roll out any puddles that form.

WARRANTY

We warrant our products to be of good quality and will replace any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. The user shall determine the suitability of the product for the intended use and assume all risks and liability in connection therewith. Therefore, except for such replacement of product, Cornerstone Coatings makes no warranty or guarantee express or implied including warranties of fitness for a particular purpose or merchantability, respecting its products, and Cornerstone Coatings shall have no other liability with respect thereto. This warranty supersedes all other warranties express or implied.