

Pickup Derby

½ Ton 2 wheel drive ONLY

1. All interior and exterior trim must be removed.
2. Battery must be relocated to passenger compartment.
3. Gas tank must be relocated to inside box behind cab.
4. Transmission coolers may be used. Must be safe.
5. Engine cradles, trans braces, non-stock drive shafts may be used.
6. No metal may be added other than stated in the rules.
7. Absolutely no welding or plating of frame.
8. Dash bar and behind the seat bar required. Full cage recommended.
9. Doors must be welded or chained.
10. Box may be bolted to frame in 6 additional locations, ¾ bolts max. 6" washers max.
11. Box may be welded to the cab. 1" x 1/4 " strap max.
12. Tailgate may be welded in place. No metal added.
13. Rear bumper may be welded to the box/tailgate, 1"x1/4" strap max.
14. 1" max threaded rod may be used at core support, may be weld to frame and run through hood. 6" washer on hood max. Sides of hood may be bolted or chained. No structural metal added.
15. 12"x12" minimum access hole must be in hood.
16. Rear hood springs must remain in place.
17. Any stock front bumper may be used. May be welded tight to frame. No metal added. If bumper is welded tight to frame all factory brackets must be removed.
18. Only 5 or 6 lug rear ends may be used. NO FULL FLOATING AXLES.
19. Rear suspension must bounce.
20. Front suspension may be bolted solid ¾" max. Bolt may be welded into place. No additional weld or metal may be added.
21. Fenders may be bolted 2 places each max.
22. Any rubber tire may be used, must be round and black.