

## Herby Derby Rules

- 1) Any make/model car may be used as long as it has a 108" wheel base or smaller, this will include front, rear, and all wheel drive models.
- 2) Cars can have 6 cylinder engine or less.
- 3) Cars must have all trim, upholstery, and glass removed (not broken), this excludes dash/column and drivers seat.
- 4) No extra welding or modifications of any type may be added to cars other than stated in rules, used cars may be straightened or fixed WITH-IN REASON, call first!!
- 5) Stock cooling systems only, new/replacement radiators allowed.
- 6) Trunk/decklid or hatchbacks may be removed or chained at four points max.
- 7) Doors may be chained at four points max, except drivers door may be welded at four points, 6" welds max.
- 8) Hoods may be chained and/or bolted at four points max, bolts may not contact any part of frame. 3/4" bolts max. Fire/inspection hole must be cut into hood 12"x12" minimum
- 9) ALL CARS MUST HAVE FUNCTIONING BRAKES upon entry in arena.
- 10) Any AIR filled tire may be used, flaps allowed, valve stem protectors allowed.
- 11) Driver Safety: A bar (pipe or tubing no larger than 6" diameter) is recommended behind drivers seat but not required. Dash bars are also allowed. Bars may be welded in place using no larger than 6"x6"x1/4" plate. Bars or plate may not contact any part of frame. Drivers window net may be welded or bolted into place. Windshield bars may be welded or bolted into place (2 max). All cars must have functioning seat belts.
- 12) Batteries MUST be removed from engine compartment and relocated into drivers compartment. Original key switch and necessary dash/ECM components may remain in stock locations.
- 13) Fuel tanks MUST be removed from factory locations. Fuel tank must be placed behind drivers seat. Any type fuel tank may be used, MUST BE SAFE!! If original tank is used tank must be secured using metal straps or chain and covered with blanket. Please call with any questions.
- 14) Any 6 cylinder or less engine/transmission may be used. Engine may be welded or chained into place but cannot reinforce frame/car in any way.
- 15) Stock rearend and drive train components only.
- 16) No welding or reinforcing frame allowed other than stated in rules. Call if fixing used cars.
- 17) All suspension must remain stock and bounce. No chaining of suspension will be allowed.
- 18) Bumpers must remain stock, front bumper may be welded or chained to prevent falling off but absolutely no metal may be added other than weld.

19) All judges decisions are final. Call with any questions, leave message. Shannon (701)308-0668