

G-8000
G-8500



Stronger for longer[®]

GARAGA

INDUSTRIAL



INDUSTRIAL

G-8000 G-8500

Colour and Panel style



Ice White
With grooves

Available sizes

Widths:

From 6 ft. to 24 ft., in 1-inch increments
(From 1.8 m to 7.3 m, in 25 mm increments)

Heights:

From 8 ft. to 18 ft., in 3-in. increments
Note: 8'3", 8'6" and 10'3" are not available
(From 2.4 m to 5.5 m, in 76 mm increments)

Standard features


Exterior steel	24-gauge, hot dipped-galvanized steel
Exterior surface	Finely embossed woodgrain design Deep ribbed steel for extra sturdiness
Finish	Baked-on polyester paint. Can be painted
Colour	Available in Ice White (QC-7207)
Panel Thickness	2" (50 mm)
Model G-8500	CFC-free Polystyrene; R-Value 6.6 (RSI:1.2)
Model G-8000	Non-insulated
Weatherstripping	Flexible EPDM bottom
Center & End stiles	20-gauge galvanized steel attached by a Tog-L-Loc® joining system with no rivets at hinge placement locations.
Tracks	13 or 14-gauge; 2" (50 mm) commercial tracks for doors less than 140 sq ft (13 sq m) 12-gauge; 3" (76 mm) industrial tracks for doors above 140 sq ft (13 sq m)
Springs	Torsion type

Technical specifications and shop drawings for the G-8000 and G-8500 doors are available on this webpage: www.garaga.com/en/industrial


Garaga warrants that the G-8500 and G-8000 products will be free from defects in workmanship and material for one year from the time of installation.

Garaga has established a permanent research program for all its products. As a result of this ongoing quest for improvement, technical specifications for various door systems are subject to change without notice.

Windows



Sealed clear plain glass window 1/8 inch (3 mm) is inserted into an expanded PVC frame which is cast without joints. Size: 21 X 13 in. (533 X 330 mm).



Tongue & groove joint

20 gauge galvanized steel center and end stiles.

24 gauge, G-40 galvanized steel type (Z-120).

1 7/16 in polystyrene insulation with protective PVC backing for G-8500.

Flexible bottom weatherstripping that ensures the weather-tightness of the threshold

CERTIFIED
ISO 9001



GARAGA Inc.

8500, 25th Avenue St-Georges, QC Canada G6A 1K5

Telephone: **(418) 227-2828** Fax: (418) 227-6282 E-mail: info@garaga.com

www.garaga.com



Products manufactured in Canada

© Garaga Inc. 2006 - All rights reserved