



Winged Slats®

Winged Slat® provides increased privacy over most other slats. These self-locking slats (no locking channels are needed) combine the proven quality and durability of our standard slats with unique “wings” for extra screening and security. This uniquely styled, patented slat can be purchased by the bag or pre-inserted into the chain link wire during the weaving process.

Design – Includes a rigid, flat tubular body with inside “legs” for extra support. These flexible and resilient wing portions are positioned on each side of the slat body. Serrations are added to the wings for easier installation and locking power.

Installation – Insert the slats vertically into the fence from top to bottom. No tools are necessary. The serrated wings grip the knuckles of the wire mesh securing the slat in place.

Standard Heights – 4 ft., 5 ft., 6 ft., 7 ft., and 8 ft. For heights exceeding 7 feet, we recommend using (2) two half sizes (i.e. for 10 foot fence use two 5 foot slats)

Special heights available upon request

Slat Length – 2” shorter than the overall height of the fence

Wind Load and Privacy Factor – Approximately 90% (Based on wire/mesh used-stretch tension)

Colors – Beige, Redwood, Black, White, Royal Blue, Forest Green, Gray, Dark Brown, Sky Blue

Features and Benefits

Materials – SlatSource® slats are extruded from High Density Polyethylene (HDPE), color pigments and ultra violet (UV) inhibitors specifically formulated to retard the harmful effects of the sun and lengthen the life of the slat.

Durability – Our slats are also resistant to severe weather conditions, salt water, sand, road dirt, most acids, alcohol, alkaline, ammonia, petroleum distillates, and common environmental pollutants.

Maintenance – Our slats are nearly maintenance free. They may be pressure cleaned of surface contaminants with plain water.

Wind Load Disclaimer – We will not be held responsible for fence damage resulting from wind load conditions due to insufficient structural support.

Designations – Meets ASTM Designation: F3000/F3000M (except HedgeLink and Aluminum Slat)



HDPE Technical Properties

Property	Values
Melt Index	(.6) A low melt index indicates improved stress and crack resistance.
Density	(.957) Polyethylene ranges anywhere from .914 to .960 in density. A higher density yields maximum stiffness without becoming overly brittle.
Minimum Temp.	(-76° F) Polyethylene stays flexible even at this temperature extreme.
Maximum Temp.	(250° F) Polyethylene does not distort until reaching this temperature.
Tensile Strength	(3,700 psi) Material will not suffer distortion at lesser loads or impacts.

Slat Name	Slat Width	Mesh Size	Wire Gauge	Coverage Area
Winged Slat	1 7/16"	2" only	9 gauge only	10 Linear feet

Available Colors

(colors are approximations)



Exact representation of colors in printing is difficult. Please refer to actual color samples for accurate matching. **Samples available upon request.**



A PrivacyLink® Company

1.888.806.7528

www.slatsforchainlinkfence.com

info@eprivacylink.com

Many patents and patents pending.