
SAFETY DATA SHEET DP-114, Corrosion Inhibitor

Page: 1
Printed: 03/21/2014
Revision: 10/09/2012

Pumping Jack Chemicals, Inc. 35203 E. 114th Earlsboro, OK 74840



1. Product and Company Identification

Product Code: DP-114

Product Name: DP-114, Corrosion Inhibitor

Trade Name: Oil Soluble Corrosion Inhibitor

Manufacturer Information

Company Name: Pumping Jack Chemicals, Inc.

Phone Number: (405)382-7930 **Fax Number:** (405)382-1787

Emergency Contact: Mike Atchley (405)659-0379 **Alternate Emergency Contact:** Dawn Elder (405)659-1209

Email address: pjc1521@yahoo.com

2. Hazards Identification

GHS Classification Placard Key word GHS hazard phrase
Serious Eye Damage/Eye Irritation, Category Exclamation Placard Warning Causes serious eye irritation

GHS Hazard Phrases

H304: May be fatal if swallowed and enters airways

H225: Highly flammable liquid and vapor

H319: Causes serious eye irritation

H335: May cause respiratory irritation.

GHS Precaution Phrases

P233: Keep container tightly closed.

P210: Keep away from {heat/sparks/open flames/hot surfaces}. - No smoking.

P280: Wear protective gloves/clothing and eye/face protection as specified by the manufacturer/supplier or the competent authority.

P264: Wash hands thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

GHS Response Phrases

P331: Do NOT induce vomiting.

P370+378: In case of fire, use ... for extinction ... appropriate media specified by the manufacturer/supplier or the competent authority - if water increases risk.

P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+313: If eye irritation persists, get medical advice/attention.

P309+311: Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

GHS Storage and Disposal Phrases

P501: Dispose of contents/container to ... (in accordance with local/regional/national/international regulation).

P403+235: Store in cool/well-ventilated place.

P403+233: Store container tightly closed in well-ventilated place - if product is as volatile as to generate hazardous atmosphere.

SAFETY DATA SHEET DP-114, Corrosion Inhibitor

Page: 2 Printed: 03/21/2014 Revision: 10/09/2012

Potential Health Effects (Acute and Chronic)

Inhalation

May cause irritation of the respiratory tract.

Skin Contact

Irritating. Prolonged contact may result in absorption.

Eye Contact

Causes severe eye irritation.

Ingestion

May cause abdominal discomfort.

Medical Conditions Generally Aggravated By Exposure

None known

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

3. Composition/Information on Ingredients

На	zardous Components (Chemical Name)	CAS#	Concentration
1.	Solvent naphtha medium aliphatic	64742-88-7	66.0 %
2.	Isopropyl alcohol	67-63-0	6.0 %
3.	Phenol, p-tert-butyl-, polymer with ethylene oxide, formaldehyde and propylene	30704-64-4	3.0 %
4.	Amidoimidazoline	NA	10.0 %
5.	Fatty Acid Mixture	NA	15.0 %

4. First Aid Measures

Emergency and First Aid Procedures

Eyes: Flush eyes with plenty of water for at least {15} minutes, occasionally lifting the upper and lower eyelids. Skin: Flush skin with plenty of water for at least {15} minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Ingestion: If victim is conscious and alert, give {2-4} cupfuls of milk or water. Never give anything by mouth to an unconscious person. Inhalation: Remove from exposure and move to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

In Case of Inhalation

Remove victim to fresh air. Consult a physician.

In Case of Skin Contact

Remove contaminated clothing. Wash skin with soap and water.

In Case of Eye Contact

Immediately flush eyes with plenty of water for at least 15 minutes.

In Case of Ingestion

If patient is conscious, give 2 glasses of water, do not induce vomiting. : If patient is unconscious, seek medical attention.

Note to Physician

Treat symptomatically and supportively.

Signs and Symptoms Of Exposure

Repeated skin contact may cause dermatitis.

5. Fire Fighting Measures

Flash Pt: > 142.00 F Method Used: TAG Closed Cup

Explosive Limits: LEL: .7 UEL: 6

Autoignition Pt: > 487.00 C

SAFETY DATA SHEET DP-114, Corrosion Inhibitor

Page: 3 Printed: 03/21/2014 Revision: 10/09/2012

Fire Fighting Instructions

As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

Flammable Properties and Hazards

Vapors may travel to source of ignition and flash back. Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Many liquids are lighter than water.

Hazardous Combustion Products

May form Carbon Monoxide and Carbon Dioxide.

Suitable Extinguishing Media

Dry chemical, CO2, sand, earth, water spray or regular foam.

Unsuitable Extinguishing Media

None known.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled

Use proper personal protective equipment as indicated in Section {8}. Spills/Leaks: Clean up spills immediately, observing precautions in the Protective Equipment section. Sweep up or absorb material, then place into a suitable clean, dry, closed container for disposal. Avoid generating dusty conditions. Provide ventilation.

Protective Precautions, Protective Equipment and Emergency Procedures

Safety glasses Rubber or neoprene gloves Eye wash station in work area Wash hands after use. Do not smoke. Launder contaminated clothing.

Environmental Precautions

Immediately contain spills with inert material, and absorb with sand or other absorbent.

7. Handling and Storage

Precautions To Be Taken in Handling

Wash thoroughly after handling Remove contaminated clothing and wash before reuse. Use with adequate ventilation. Avoid contact with eyes, skin, and clothing. Keep container tightly closed. Avoid ingestion and inhalation.

Precautions To Be Taken in Storing

Keep container closed when not in use. Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible substances. Do not reuse this container.

8. Exposure Controls/Personal Protection									
Hazardous Components (Chemical Name) CAS #		CAS#	OSHA PEL	ACGIH TWA	Other Limits				
1.	Solvent naphtha medium aliphatic	64742-88-7	No data.	No data.	No data.				
2.	Isopropyl alcohol	67-63-0	PEL: 400 ppm	TLV: 200 ppm STEL: 400 ppm	No data.				
3.	Phenol, p-tert-butyl-, polymer with ethylene oxide, formaldehyde and propylene	30704-64-4	No data.	No data.	No data.				
4.	Amidoimidazoline	NA	No data.	No data.	No data.				
5.	Fatty Acid Mixture	NA	No data.	No data.	No data.				

Respiratory Equipment (Specify Type)

Use a NIOSH/MSHA or European Standard EN {149} approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Eye Protection

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in {29} CFR {1910.133} or European Standard EN166.

SAFETY DATA SHEET DP-114, Corrosion Inhibitor

Page: 4 Printed: 03/21/2014 Revision: 10/09/2012

Protective Gloves

Wear appropriate protective gloves to prevent skin exposure.

Other Protective Clothing

Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls (Ventilation etc.)

Use adequate ventilation to keep airborne concentrations low.

Work/Hygienic/Maintenance Practices

Wash thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice.

Environmental Exposure Controls

Use with adequate ventilation.

9.	Physical and Chemical Properties
Physical States:	[] Gas [X] Liquid [] Solid
Melting Point:	No data.
Boiling Point:	> 320.00 F
Autoignition Pt:	> 487.00 C
Flash Pt:	> 142.00 F Method Used: TAG Closed Cup
Explosive Limits:	LEL: .7 UEL: 6
Specific Gravity (Water = 1):	.8889
Vapor Pressure (vs. Air or mm Hg):	< 1.0
Vapor Density (vs. Air = 1):	4.5
Evaporation Rate:	N/A
Solubility in Water:	Negligible
Solubility Notes	
Negligible in water	
Percent Volatile:	N.A.
Appearance and Odor	
Brownish	
distinctive odor	

10. Stability and Reactivity

Stability: Unstable [] Stable [X]

Conditions To Avoid - Instability

Stable as supplied.

Incompatibility - Materials To Avoid

Plastic containers.

Hazardous Decomposition Or Byproducts

Carbon Dioxide and Carbon Monoxide

Possibility of Hazardous Will occur [] Will not occur [X]

Reactions:

Conditions To Avoid - Hazardous Reactions

Sources of ignition.

SAFETY DATA SHEET DP-114, Corrosion Inhibitor

Page: 5
Printed: 03/21/2014
Revision: 10/09/2012

11. Toxicological Information

Toxicological Information

Route of Exposure: Skin - May cause skin irritation. Skin absorption - May be harmful if absorbed through skin. Eye contact - May cause eye irritation. Inhalation - Harmful if swallowed.

Hazardous Components (Chemical Name)	CAS#	NTP	IARC	ACGIH	OSHA
1. Solvent naphtha medium aliphatic	64742-88-7	n.a.	n.a.	n.a.	n.a.
2. Isopropyl alcohol	67-63-0	n.a.	3	A4	n.a.
3. Phenol, p-tert-butyl-, polymer with ethylene oxide, formaldehyde and propylene	30704-64-4	n.a.	n.a.	n.a.	n.a.
4. Amidoimidazoline	NA	n.a.	n.a.	n.a.	n.a.
5. Fatty Acid Mixture	NA	n.a.	n.a.	n.a.	n.a.
Carcinogenicity:	NTP? No	IARC Monographs? No		OSHA Regulated? No	

12. Ecological Information

General Ecological Information

Biodegradation - Material expected to be readily biodegradable. Hydrolysis - Material transformation to Hydrolysis not expected to be significant. Photolysis - Material transformation due to Photolysis not expected to be significant. Atmospheric Oxidation - Material expected to degrade rapidly in air.

13. Disposal Considerations

Waste Disposal Method

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in {40} CFR Parts {261.3}. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. Transport Information

LAND TRANSPORT (US DOT)

DOT Proper Shipping Name Petroleum distillates, n.o.s. [or] Petroleum products, n.o.s.

DOT Hazard Class: 3

DOT Hazard Label: COMBUSTIBLE LIQUID

UN/NA Number: UN1268

Packing Group: III

Precautionary Label DANGER!

Additional Transport Information

DOT not regulated in containers of less than 118.9 gallons.

15. Regulatory Information

Regulatory Information

All chemical substances in this material do not excede a reporting threshold under TSCA or SARA Section 302-304-311-313.

16. Other Information

For industrial use only. All information appearing herein is based on data obtained from recognized technical sources. While the information is believed to be accurate, Pumping Jack Chemicals makes no representations as to its accuracy or its sufficiency. Conditions of use are beyond our control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their purpose and they assume all risks of their use, handling, and disposal of the product are from the publication or use of or reliance upon information contained herein.

Revision Date: 10/09/2012